


PPL1-T Thermocouple with Lead

Our PPL1 sensor is designed for a wide range of general purpose industrial applications that require a flying lead sensor. Our flexibility allows us to manufacture a sensor to your requirements including all common thermocouple types and simplex or duplex sensing elements. Various common options are shown on this data sheet but this is not an exhaustive list, please contact us with your requirements. Full details of the lead types and accessories are available in the appropriate data sheet. UKAS or traceable calibration is available upon request.




Specifications	
Sensor Type	Type J, K or T thermocouple. Insulated or Grounded hot junction.
Operating Range	Limited to range of lead as standard— see below— can be extended at additional cost
Sheath Material	316 stainless steel
Tolerance Band	BS EN 60584-2:1993 Class 1 or Class 2 (Determined by material availability)
Wiring System	Simplex or Duplex
Lead Types	A—PVC/PVC Screened (-10 to +105°C) B—PTFE/PTFE Screened (-75 to +250°C) C—Glass Fibre Stainless Steel Overbraid (0 to 350°C) Other cables available upon request).

Full details of all our products can be seen on our web-site:

www.processparameters.co.uk

PPL1-T Thermocouple with Lead



NOTE: Some sheath diameter / lead type combinations require a pot seal. A duplex sensor may have two separate cables.
Some option combinations not possible

This data sheet gives details of the most popular options available for this type of sensor but is not intended to give an exhaustive list of possibilities. If you have a special requirement, please contact our sales office for assistance.

Process Parameters Ltd

Unit 11C, Waldeck House, Waldeck Road, Maidenhead, Berkshire, SL6 8BR

Tel: 01628 778688

Fax: 01628 777714

Email: sales@processparameters.co.uk

Web: www.processparameters.co.uk