




**"ALL-STAINLESS" SOLID-FRONT PRESSURE GAUGES, TYPE PBX-SF-HP**

**TYPE PBX-SF-HP, full safety pattern according to EN 837-1**

**STANDARD MODEL**

|                     |   |                 |  |
|---------------------|---|-----------------|--|
| <b>CASE</b>         | : bayonet lock, AISI304/1.4301, IP-65<br>solid front & blow-out back acc. to EN 837-1 | <b>RANGE</b>    | : 0 - 4000 bar upto 0 - 6000 bar<br>for higher ranges (max. 7000 bar): see below |
| <b>WETTED PARTS</b> | : spiral wound tube, HP160  | <b>ACCURACY</b> | : ± 1.0% F.S./class 1<br>± 0.6% F.S./class 0.6 on demand                         |
| <b>WINDOW</b>       | : safety glass  | <b>MOVEMENT</b> | : AISI304/1.4301   |
| <b>DIAL</b>         | : aluminium, black figures on white   |                 |  |
| <b>POINTER</b>      | : aluminium, black  |                 |  |
| <b>CONNECTION</b>   | : 9/16" UNF x18 H.P. female, AISI316Ti, 1.4571  |                 |  |

| TYPE         | MODEL   | CASE DIAMETER ( Ø in mm) |
|--------------|---|--------------------------|
|              |   | 160                      |
| <b>A</b>     |    | PBX-SF-HP160XA           |
| <b>B</b>     |   | PBX-SF-HP160XB           |
| <b>D</b>     |  | PBX-SF-HP160XD           |
| OPTIONS      |   | EXTRA COSTS              |
| <b>Lx</b>    | LIQUID FILLED CASE:<br>GLYCERINE  | PBX-SF-HP160Lx           |
| <b>Range</b> | 0 - 7000 bar  |                          |