



OPTIONS FOR SECUTHERM® THERMOMETERS						
OPTION		CASE DIAMETER (Ø in mm)				
		63	80	100	160	250
SILICONE OIL FILLING	<i>AGAINST HEAVY VIBRATIONS</i>					
CASE MATERIAL AISI316/1.4401 <small>(i.o. AISI304/1.4301)</small>	<i>CASE + BAYONETRING</i> <i>FRONT -OR BACKFLANGE</i>	N.A.	N.A.			N.A. N.A.
ANTI-VIBRATIONSPRING <small>for model: TXR, Type A and E SEE ALSO TXR-DIESEL</small> +AVS	A  E 	+AVS	+AVS	+AVS	+AVS	+AVS
PLEXIGLASS	<i>PMMA</i>					
"SECURIT" GLASS	<i>SAFETY GLASS</i>					
DRAG POINTER	<i>RESETABLE WITH KEY</i>					
DRAG POINTER IN COMBINATION WITH CONTACT	<i>RESETABLE WITH KEY ONLY FOR "HZ" CONTACTS</i>	N.A.	N.A.			N.A.
OVERLOAD RESISTANCE EXECUTION	<i>OVERLOAD POSSIBLE UPTO 100% DEPENDING ON RANGE MAXIMUM +800°C</i>					
STAINLESS STEEL MOVEMENT	<i>AISI304/1.4301</i>					
MICROMETER POINTER	<i>ADJUSTABLE POINTER</i>					