

# BUILT-IN LOW-ACTION CONTACT TYPE S

## TYPE S Hz

<b>INSTRUMENT</b>	: class 1
<b>MINIMAL RANGE</b>	: 60 °C
<b>CONNECTOR</b>	: cable junction box, SEE BELOW
<b>HYSTERESIS</b>	: max. 1% up and down
<b>SETPOINT(S)</b>	: from outside with key
<b>WINDOW</b>	: PMMA - plexiglass
<b>POINTER</b>	: black (adjustable see page 24)
<b>CONTACT POINTER(S)</b>	: red

example:

TXR100XA  
+ S-12 Hz



### ELECTRICAL SWITCH CAPACITY

<b>AC</b>	: 18 VA (max. 250V)
<b>DC</b>	: 10 W (max. 250V)

CONTACT TYPE	SWITCH FUNCTION	CABLE JUNCTION BOX	CASE DIMENSIONS				
			100	160	96x96	144x144	72x144
<b>S-1 Hz</b>		 Hirschmann					
<b>S-2 Hz</b>							
<b>S-3 Hz</b>							
<b>S-11 Hz</b>							
<b>S-12 Hz</b>							
<b>S-21 Hz</b>							
<b>S-22 Hz</b>							
<b>S-xx Hz +GS</b>	 example: S-21 Hz GS	 Wiebrock					
<b>S-33 Hz</b>							N.A.
<b>S-33 Hz+GS</b>							N.A.
<b>S-xxx Hz</b>	function to be specified at order						N.A.
<b>S-xxxx Hz</b>	function to be specified at order		O.D.	O.D.	O.D.	O.D.	N.A.
OPTION			EXTRA COSTS				
<b>Lx</b>	<b>LIQUID FILLED CASE (ONDINA)</b>				N.A.	N.A.	N.A.