

BUILT-IN ELECTRONIC CONTACT TYPE E

TYPE E Hz

INSTRUMENT	: class 1
MINIMAL RANGE	: 60 °C
CONNECTOR	: cable junction box, SEE BELOW
HYSTERESIS	: max. 1% up and down
SETPOINT(S)	: from outside with key
WINDOW	: PMMA - plexiglass
POINTER	: black (adjustable see page 24)
CONTACT POINTER(S)	: red

example:

TXR100XA
+ E-12 Hz



ELECTRICAL SWITCH CAPACITY

Nominal voltage	: 10...30 V dc
Proximity sensor	: Si-K08-AP7 (Turck)
Output	: 3-wire, PNP
Regulations	: EN 60947-5-2

CONTACT TYPE	SWITCH FUNCTION	CABLE JUNCTION BOX	CASE DIMENSIONS				
			100	160	96x96	144x144	72x144
E-1 Hz		<p>Hirschmann</p>					
E-2 Hz							
E-11 Hz							
E-12 Hz							
E-21 Hz							
E-22 Hz							
E-xxx Hz	function to be specified at order	<p>Wiebrock</p>	O.D.	O.D.	O.D.	O.D.	N.A.
E-xxxx Hz	function to be specified at order		O.D.	O.D.	O.D.	O.D.	N.A.
OPTION			EXTRA COSTS				
Lx	LIQUID FILLED CASE (ONDINA)				N.A.	N.A.	N.A.